

SIKAFLOOR

Product Selection Guide



BUILDING TRUST

| | Moisture Barrier | Primer | Smoothing & Ramping Mortars | | Levelling Compounds | | | | |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-------------------------------------------|----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|-------------------------------------------------------------------------------|
| | | | | | | | | | |
| | 158W Fast Barrier | Prep N Prime | Pro Finish | Ramp & Patch | Level Top | Level Eco | Level 30 | Level Ultra | 4020 Fibre Level |
| | Rapid drying, odourless epoxy barrier that chemically cures to protect from rising subfloor moisture but also from liquids penetrating into concrete. | Designed to prime nonporous surfaces including vinyl, terrazzo, glazed tiles, epoxy coatings, steel & acrylic membranes. | Fast-drying, smoothing and self-priming skim coat. | Sikafloor Ramp & Patch is a fast setting ramping /patching mortar used for internal and external concrete surfaces. | High-flow self levelling compound with great workability and low shrinkage. | Economical high-build levelling compound. | Industrial self-levelling compound with a fully trafficable surface once sealed to withstand forklift traffic. | Premium, high performing, fiber reinforced levelling compound. | Fast drying fiber reinforced levelling compound for semi-flexible substrates. |
| Build | | | 0 – 8mm | 1 – 50mm | 1 – 30mm | 3 – 75mm | 3 – 30mm | 1 – 50mm | 3 – 20mm |
| Porous | ✓ | | | | | | | | |
| Non-Porous | | ✓ | | | | | | | |
| Use Type | | | | | | | | | |
| Domestic | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Commercial | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Industrial | ✓ | | | | | | ✓ | | |
| Substrate type | | | | | | | | | |
| Internal Concrete | ✓ | | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ |
| External Concrete | ✓ | | | | | | ✓ | ✓ | |
| Timber or CFC Sheet | | | | | | | | | ✓ |
| Underfloor Heating | ✓ | | ✓ | | | | | ✓ | ✓ |